

# MX

## ECOBULK MX

Perfect for transport and storage.



- Approved for filling products of a maximum density of 1.9
- Perfectly suited for high bay warehousing
- Can be stacked up to 4-high
- Reinforced, warp resistant tubular steel grid jacket
- Additional corner guards to protect the inner container
- Available in a variety of equipment packages

Please do not hesitate to contact us regarding any technical concerns or questions.

**SCHÜTZ**  
PACKAGING SYSTEMS

www.schuetz.net

### MATERIAL

#### Inner bottle

- Extrusion blow-moulded HDPE
- SMP protective barrier (optional)
- Additional UV and light protection of the filling product (optional)


#### Outer container

- Welded tubular steel grid, galvanized

#### Bottom plate

- To provide stability and to facilitate minimum residual contents from the inner container

### PALLETS (4-way entry)



### CERTIFICATIONS

- UN 31 HA1/Y (optional)
- Maximum density 1.9
- SCHÜTZ FOODCERT (optional)
- System certification for food (contains materials that are FDA compliant)

### CAPACITY

- MX 640
- 640 litres (170 gal)
- MX 820
- 820 litres (220 gal)
- MX 1000
- 1,000 litres (275 gal)
- MX 1250
- 1,250 litres (330 gal)

### FILLING OPENING

- DN 150 with screw cap
- DN 225 with screw cap
- DN 400 with clamp-ring lid (only for MX 1000)

### OUTLET VALVES


- Integrated butterfly valve DN 50, DN 80
- Screwable butterfly valve DN 50, DN 150
- Screwable ball valve DN 50

### DIMENSIONS

- MX 640
- 1,200 x 800 x 1,000 (L x W x H)
- MX 820
- 1,200 x 1,000 x 1,000 (L x W x H)
- MX 1000
- 1,200 x 1,000 x 1,160 (L x W x H)
- MX 1250
- 1,200 x 1,000 x 1,350 (L x W x H)

### DYNAMIC LOAD

Filled ECOBULK according to the specific weight of the filling goods



### WEIGHT

- MX 640
- 48 kg (plastic)
- MX 820
- 51 kg (steel), 54 kg (plastic)
- MX 1000
- 56 kg (steel), 59 kg (plastic & full-plastic)
- MX 1250
- 65 kg (steel), 68 kg (plastic)

### STATIC LOAD

Max. 4-high

